

solvoprint nolite 350 CA

Technical Information

➤ General Information

- CA version with improved coating
- approx. 375 µm polyester compound
- matt, special inkjet coating
- good scratch- and water resistance after complete drying
- good stiffness (no side curl)
- opaque and highly dimensionally stable with bright grey backside

➤ Areas of Application

- suitable for eco solvent, real solvent and UV curable ink systems
- especially for Display Systems (Pop-Up or similar)
- suitable for indoor and for short term outdoor application use
- application without laminating is possible; laminating is recommended for extra protection

➤ Processing & Handling

- to avoid fingerprints, usage of cotton gloves is recommended
- for protective purpose usage of Neschen Protective Laminates is recommended (ensure adequate drying before lamination) – drying time of min. 12 hours is recommended.
- please notice Handling- and Storage Conditions in our catalog or visit our homepage www.neschen.de
- storage is best to be done in the original case

➤ Advantages / Special Features

- very good colour reproduction and excellent print quality
- multi-purpose but especially for Pop-Up - and other display systems
- part of Neschen's Display Graphics Solutions (DGS)
- quick drying with normal ink load
- for more information see the latest Neschen compatibility list (at www.neschen.de)

➤ Technical Data

➤ Carrier:

carrier material:	polyester compound	
thickness [µm]:	approx. 370 - 380	approx. 15 mil
weight [g/m²]:	approx. 490	
gloss level:	matt coating	
whiteness: [Lab]		

➤ More informations:

storage conditions:	original boxed at 10 – 35°C
material durability [months]:	18 months
temperature resistance:	