



printex art canvas 340 premium

Technical Information

➤ General Information

- cotton – polyester blend fabric
- 340 g/m² heavy linen weave
- topgrade inkjet coating for waterbased inks
- print- and back side with a matt, white surface

➤ Areas of Application

- suitable for thermal and piezo printers
- printable with dye based and pigmented inks
- suitable for indoor applications
- perfect for ambitious art reproduction
- especially for stretched canvases, suitable for other frames

➤ Processing & Handling

- to avoid fingerprints, usage of cotton gloves is recommended
- please notice Handling - and Storage Conditions in our catalog or visit our homepage www.neschen.de
- storage is best to be done in the original case
- drying time of min. 12 hours is recommended before processing

➤ Advantages / Special Features

- bright colours and good printing quality
- good scratch resistant
- quick drying
- beautiful canvas effect and almost no cracking by special coating
- for more information see the latest Neschen compatibility list (at www.neschen.de)



printex art canvas 340 premium

Technical Information

➤ Technical Data

➤ Carrier:

Carrier material:	cotton – polyester blendet fabric		
Weight [g/m²]:	approx.: 370		
Thickness [µm]:	approx. : 480		
Tear force[N/15mm]:	md: > 350	cd: > 175	DIN 53455
Elongation at tear [%]:	md: > 15	cd: > 15	DIN 53455
Tear resistance[N/mm²]:	md: > 45	cd: > 20	DIN 53455

➤ Others:

Shelf Life [Months]:	18
Temperature Stability:	10 - 35°C / 50 to 95°F at 30 to 65% humidity
Fire protection:	no flame retardant preparation!

All tests were performed in accordance with 23/50-2, DIN 50014.

Temperatures in Fahrenheit and thicknesses in mil are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice. Neschen has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administrations's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the Neschen directions for use, these products should not present a health and safety hazard. However, use or processing of the products is manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards.