



printlux backlit

Technical Information

➤ General information

- 135µm polyester film
- front side glossy, reverse side satin finish (with special InkJet coating)
- front side scratch-resistant and waterproof
- dimensionally stable
- translucent

➤ Areas of application

- suitable for thermal and piezo printers
- designed for dye based inks
- for indoor applications; with proper protection outdoor applications possible
- for lightbox and backlight applications

➤ Processing & Handling

- please notice Handling- and Storage Conditions in our catalog or visit our homepage www.neschen.de
- to avoid fingerprints, protective gloves are best to be worn while handling
- storage is best to be done in the original case
- please note: please print on the reverse satin side only; the image should be printed mirrored

➤ Advantages / Special Features

- photorealistic print quality
- high colour brilliance, big gamut
- quick drying
- "night & day" characteristics: the print will appear brilliant & strong even without backlight
- scratch resistant front, durable coating
- for more information see the latest Neschen compatibility list (at www.neschen.de)



printlux backlit

Technical Information

➤ Technical Data

➤ Carrier:

Film type:	polyester film with inkjet coating
Thickness [µm]:	135 approx. 5,3 mil
Weight [g/m²]:	approx. 190
Opacity [%], according TAPPI T-425:	63
Whiteness [CIE Ganz 82]:	56

➤ Others:

Handling/storage conditions:	15° to 30°C / 59° to 86° F; 30 to 70% relative humidity	
Shelf life [years]:	2	
Temperature stability:	-30° to + 50°C	-22° to +122° F

All tests were performed in accordance with 23/50-2, DIN 50014.