NESCHEN ROLLCUTTER 1650



PRODUCT OVERVIEW

- Ideal for easy and safe cutting of any roll media
- Fast slitting or rewinding of any media
- Cutting off media on a roll even including its core
- High processing speed for high productivity
- External arranged brake for a better adjustment
- Fixed adjustable feet for safe working
- Heavy freestanding model
- No heavy power necessary



02/22

SPECIFICATIONS

Processing width	max. 1650 mm
Processing speed	max. 60 m/min
Roll diameter	max. 200 mm (cutting) max. 300 mm (wrapping)
Axis diameter	75 mm
Measurements H/W/D	1220 / 2220 / 700 mm
Axis load	max. 30 kg with product
Weight	115 kg netto
Electrical requirements	1N/PE 230VAC/50-60 Hz; 600W 3A





NESCHEN ROLLCUTTER 1650



PRODUCT OVERVIEW

- Ideal for easy and safe cutting of any roll media
- Fast slitting or rewinding of any media
- Cutting off media on a roll even including its core
- High processing speed for high productivity
- External arranged brake for a better adjustment
- Fixed adjustable feet for safe working
- Heavy freestanding model
- No heavy power necessary



02/22

SPECIFICATIONS

Processing width	max. 1650 mm
Processing speed	max. 60 m/min
Roll diameter	max. 200 mm (cutting) max. 300 mm (wrapping)
Axis diameter	75 mm
Measurements H/W/D	1220 / 2220 / 700 mm
Axis load	max. 30 kg with product
Weight	115 kg netto
Electrical requirements	1N/PE 230VAC/50-60 Hz; 600W 3A



